

RIFLE

CLASSIC WINDSHIELD Indian Scout and Spirit



MOUNTING INSTRUCTIONS

INTRODUCTION

These instructions contain important information regarding the proper installation and maintenance of your new RIFLE windshield. Read it completely and follow the recommendations for the most trouble free and enjoyable use. Statements preceded by the following words are of special significance.

WARNING:

means there is a possibility of injury to yourself and others if instructions are not followed.

CAUTION:

means there is a possibility of damage to the product if instructions are not followed.

NOTE:

indicates points of special interest.

Indian Spirit

INSTALLATION

Your new **CLASSIC** windshield utilizes a simple yet elegant four-point mount.

PREPARE YOUR MOTORCYCLE

1. All four fork clamps in the hardware kit are identical and will be installed onto your fork tubes. See **Figure 1**.

NOTE: It is always good idea to cover the gas tank and fender and other exposed painted parts to prevent damage from dropped brackets, fasteners, or clamps not installed in the proper location.

2. Remove and discard any spacers between the fork clamp halves.

NOTE: The clamps will not fit properly unless these spacers are removed.

3. If the turnsignals are mounted high on the forks, they will need to be lowered to just above the bottom triple tree. Loosely mount the left and right lower fork clamps to just underneath the bottom triple tree. See **Figure 1**.

Loosely mount left and right upper clamps with a distance between the lower and upper clamps of 4". See **Figure 1**.

4. Leave clamps loose enough so they can rotate on fork tubes. It is easier to tighten the inside screws first and then rotate the clamps to the proper position before the final tightening of the outside screws.

CAUTION:

Check for clearance between fork clamps and gas tank. Turn to left lock and then to right lock to make sure the clamps do not contact the gas tank or any part of the bike. If clamps are not positioned properly it increases the likelihood of contacting the tanks and damaging it.




Figure 1

MOUNT THE WINDSHIELD

1. Hold the windshield up to the fork clamps, with the windshield support brackets on the outside of the fork clamps.

2. Loosely secure the windshield with the supplied 1/4 x 20 Allen bolts and washers See **Figure 2**.

3. Adjust the windshield so there is even clearance around the headlight and gauges.

CAUTION:

Make sure that the windshield does not contact the headlight or gauges.

4. Tighten all four fork clamps securely.

5. Tighten all four windshield support bolts to the fork clamps.

CAUTION:

Again check clearance of left and right fork lock.




Figure 2

Indian Scout

INSTALLATION

Your new **CLASSIC** windshield utilizes a simple yet elegant four-point mount.

PREPARE YOUR MOTORCYCLE

1. All four fork clamps in the hardware kit are identical and will be installed onto your fork tubes. **See Figure 1.**

NOTE: It is always good idea to cover the gas tank and fender and other exposed painted parts to prevent damage from dropped brackets, fasteners, or clamps not installed in the proper location.

2. Remove and discard any spacers between the fork clamps.

NOTE: The clamps will not fit properly unless these spacers are removed.

3. If the turnsignals are mounted high on the forks, they will need to be lowered to just above the bottom triple tree. Loosely mount the left and right upper fork clamps just underneath the top triple clamps. **See Figure 1.**

4. Loosely mount left and right lower clamps with a distance between the lower and upper clamps of 4". **See Figure 1.**

5. Leave clamps loose enough so they can rotate on fork tubes. It is easier to tighten the inside screws first and then rotate the clamps to the proper position before the final tightening of the outside screws.

CAUTION:

Check for clearance between fork clamps and gas tank. Turn to left lock and then to right lock to make sure the clamps do not contact the gas tank or any part of the bike. If clamps are not positioned properly it increases the likelihood of contacting the gas tank and damaging it.




Figure 2




Figure 1

MOUNT THE WINDSHIELD

1. Hold the windshield up to the fork clamps, with the windshield support brackets on the outside of the fork clamps.

2. Loosely secure the windshield with the supplied 1/4 x 20 Allen screws and washers **See Figure 2.**

3. Adjust the windshield so there is even clearance around the headlight and gauges.

CAUTION:

Make sure that the windshield does not contact the headlight or gauges.

4. Tighten all four fork clamps securely.

5. Tighten all four windshield support bolts to the fork clamps.

CAUTION:

Again check clearance of left and right fork lock.

Mounting Hardware: Very rarely, a **RIFLE CLASSIC** windshield may not fit using the standard mounting kit. If you experience a serious installation problem, contact us at (805) 466-5880. We may already have a solution.

CAUTION:

Never allow brake fluid to come in contact with the windshield.

WARNING:

Tinted windshields are not for nighttime use unless you look over the windshield in the normal riding position.

MAINTENANCE

WINDSHIELD CLEANING - Use mild soap and water or glass cleaners like Windex and a soft cloth. Do not use solvents or abrasive cleaners. Scratches can usually be removed with plastic polish or automotive cleaner waxes.

FORK CLAMPS - The aluminum fork clamps can be polished with a recognized polish like Semichrome or any brand name mag cleaner where the label lists it being for aluminum.

SNAP CAPS - To remove a Snap cap, lift an edge with a fingernail and carefully slide a small screwdriver blade under the cap. Gently pry off. To install, press on until cap snaps in place.

WARRANTY

RIFLE PRODUCTS - This warranty applies to products manufactured or distributed by **RIFLE**, 3140 El Camino Real, Atascadero, CA 93422, (805) 466-5880, and sold by **RIFLE** and its authorized dealers. It is given to the first retail purchaser only and is not transferable to subsequent owners.

WARRANTY OBLIGATION RIFLE - warrants that it, or one of its authorized dealers, will repair or, at its option, replace any part proven to be defective in factory material or workmanship within one year (unlimited mileage) of the date of purchase. Parts repaired or replaced under this warranty are warranted only during the balance of the original warranty period. This warranty does not include any labor charges.

DISCLAIMER OF CONSEQUENTIAL DAMAGES AND LIMITATIONS OF IMPLIED WARRANTIES - To the extent the law permits, RIFLE shall not be liable under any circumstances for loss of use of the product, consequential or incidental damages. Any implied warranty arising under law, including those of merchantability and fitness for a particular purpose is limited to duration of this limited warranty.

EXCLUSIONS FROM COVERAGE - Any repairs or replacements of parts necessitated by misuse, negligence, fire, accident, damage caused by exposure to gasoline, brake fluid, harmful solvents and cleaners, paints, or repair material, use of unauthorized accessories or faulty installation, improper or unreasonable maintenance are not covered.

IMPORTANT - Some states do not allow limitations on how long an implied warranty lasts and/or limitations or exclusions of consequential or incidental damages, so the above limitations may not apply to you.

RETURNS - If you are not completely satisfied with your **RIFLE** product, we will refund the purchase price (less freight charges), subject to a restocking fee. All claims must be made within thirty days of receipt and must be accompanied by a return authorization number. Reasonable claims will be honored within this time period only. Return merchandise must be packaged properly, and be received in new or nearly new condition. This applies only to product purchased directly from **RIFLE**.

WARRANTY REGISTRATION/QUESTIONNAIRE

For your warranty to be valid, you must fill out and mail this page to RIFLE, 3140 El Camino Real, Atascadero, CA 93422

Name _____

Address _____

City _____ State _____ Zip _____

RIFLE Model Purchased: _____

Date of Purchase: _____

Where did you purchase: _____

Dealer Name and Address: _____

Your Bike Make: _____ Model: _____

Size (cc): _____ Year: _____ Color: _____

Did you consider buying a windshield/fairing other than RIFLE? _____

If yes, which one? _____

Why were you attracted to RIFLE? _____

What motorcycle magazines do you buy most?

Cycle World

Motorcyclist

Rider

M/C Consumer

Other _____

Did you install the windshield yourself? _____

What do you like least about the windshield? _____

What accessories will you buy next for your bike? _____

FOLD HERE

Stamp

RIFLE

3140 El Camino Real
Atascadero, CA 93422